

Amendments to the claims:

Claims 1-20: (canceled)

21. (currently amended) A wiper blade for cleaning windows, comprising:

a band-like, elongated, spring-elastic support element (12), whose lower band surface (13) oriented toward the window (22) has an elongated, rubber-elastic wiper strip (14), which can be placed against the window, disposed on it so that the longitudinal axes of these two parts are parallel and whose upper band surface (11) has a wind deflection strip (42) disposed on it, which extends in the longitudinal direction of the support element (12), is provided with an attach surface (54) oriented toward the main flow of the relative wind, and is made of an elastic material, ~~characterized in that~~ wherein the wind deflection strip (42, 142, 242) has two diverging legs (44, 46), viewed in transverse cross section, which are connected to each other at a common base (48) and whose free ends oriented toward the window (22) are supported on the wiper blade (10), and ~~an~~ the attach surface (54) is embodied on the outside of the one leg (44).

22. (canceled)

23. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein the profile of the cross section is the same over the entire length of the wind deflection strip (42).

24. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein the two legs (44, 46) of the wind deflection strip (142 or 242) are connected to each other by means of a wall (144 or 244) in the vicinity of the two wiper blade ends.

25. (currently amended) The wiper blade according to claim 24, ~~characterized in that~~ wherein the wall (144) is aligned essentially perpendicular to the support element (12).

26. (currently amended) The wiper blade according to claim 24, ~~characterized in that~~ wherein the outside (246) of the wall (244) encloses an acute angle (a) with the support element (12).

27. (canceled)

28. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein the free leg ends (50, 52) of the wind deflection strip (42, 142, or 242) are attached to the wiper blade (10).

29. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein the free leg ends (50, 52) of the wind deflection strip (42, 142, or 242) are glued to the wiper blade (10).

30. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein the free leg ends (50, 52) of the wind deflection strip (42, 142, or 242) are attached, preferably glued, to the support element (12) of the wiper blade (10).

31. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein the free leg ends (50, 52) of the wind deflection strip (42, 142, or 242), at least in sections, are provided with claw-like projections (56, 58), which suitably encompass the mutually opposed outer edge strips (36) of the support element (12).

32. (canceled)

33. (currently amended) The wiper blade according to claim 31, ~~characterized in that~~ wherein the a glued attachment is produced in the vicinity of the claw-like projections (56, 58).

34. (canceled)

35. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein the attach surface (54) of the wind deflection strip (42, 142, or 242) is embodied as a flute on the outer wall of the one leg (44).

36. (canceled)

37. (canceled)

38. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein a the hardness of the material for the wind deflection strip (42) is at most 40 percent greater than the hardness of the material for the wiper strip (14).

39. (currently amended) The wiper blade according to claim 21, ~~characterized in that~~ wherein a the hardness of the material for the wind deflection strip (42, 142, or 242) is at most 20 percent greater than the hardness of the material for the wiper strip (14).

40. (canceled)

41. (new) A wiper blade for cleaning windows, comprising:
a band-like, elongated, spring-elastic support element (12), whose lower band surface (13) oriented toward the window (22) has an elongated, rubber-elastic wiper strip (14), which can be placed against the window, disposed on it so that the longitudinal axes of these two parts are parallel and whose upper band surface (11) has a wind deflection strip (42) disposed on it, which extends in the longitudinal direction of the support element (12), is provided with an attach surface (54) oriented toward the main flow of the relative wind, and is made of an

elastic material, wherein the wind deflection strip (42, 142, 242) has two diverging legs (44, 46), viewed in transverse cross section, which are connected to each other at a common base (48) and whose free ends oriented toward the window (22) are supported on the wiper blade (10), and the attach surface (54) is embodied on the outside of the one leg (44), wherein the upper band surface (11) of the support element (12), in its middle section, a wiper blade part (15) of a device, which is for connecting the wiper blade (10) to a reciprocally driven wiper arm (16), is supported, wherein an end cap (38) is respectively disposed at both ends of the support element (12), and wherein a section (40) of the wind deflection strip (42) is disposed between each respective end cap (38) and the device piece (15).

42. (new) A wiper blade for cleaning windows, comprising:
a band-like, elongated, spring-elastic support element (12), whose lower band surface (13) oriented toward the window (22) has an elongated, rubber-elastic wiper strip (14), which can be placed against the window, disposed on it so that the longitudinal axes of these two parts are parallel and whose upper band surface (11) has a wind deflection strip (42) disposed on it, which extends in the longitudinal direction of the support element (12), is provided with an attach surface (54) oriented toward the main flow of the relative wind, and is made of an elastic material, wherein the wind deflection strip (42, 142, 242) has two diverging legs (44, 46), viewed in transverse cross section, which are connected to each

other at a common base (48) and whose free ends oriented toward the window (22) are supported on the wiper blade (10), and the attach surface (54) is embodied on the outside of the one leg (44), wherein the two legs (44, 46) of the wind deflection strip (142 or 242) are connected to each other by means of a wall (144 or 244) in the vicinity of the two wiper blade ends, and wherein the wall (144 or 244) is provided with a recess (146 or 246) that is open at the edge oriented toward the window (22), wherein the width (148) of this recess is greater than the width (150) of the wiper strip (14) in a vicinity of the support element and its depth (152) reaches to the upper band surface (11) of the support element (12).

43. (new) A wiper blade for cleaning windows, comprising:

a band-like, elongated, spring-elastic support element (12), whose lower band surface (13) oriented toward the window (22) has an elongated, rubber-elastic wiper strip (14), which can be placed against the window, disposed on it so that the longitudinal axes of these two parts are parallel and whose upper band surface (11) has a wind deflection strip (42) disposed on it, which extends in the longitudinal direction of the support element (12), is provided with an attach surface (54) oriented toward the main flow of the relative wind, and is made of an elastic material, wherein the wind deflection strip (42, 142, 242) has two diverging legs (44, 46), viewed in transverse cross section, which are connected to each

other at a common base (48) and whose free ends oriented toward the window (22) are supported on the wiper blade (10), and the attach surface (54) is embodied on the outside of the one leg (44), wherein the free leg ends (50, 52) of the wind deflection strip (42, 142, or 242), at least in sections, are provided with claw-like projections (56, 58), which suitably encompass the mutually opposed outer edge strips (36) of the support element (12), and wherein the claw-like projections extend from the leg ends (50, 52) into a vicinity of a wall (154 or 254), and suitably encompass end regions (112) of the support element (12).

44. (new) A wiper blade for cleaning windows, comprising:

a band-like, elongated, spring-elastic support element (12), whose lower band surface (13) oriented toward the window (22) has an elongated, rubber-elastic wiper strip (14), which can be placed against the window, disposed on it so that the longitudinal axes of these two parts are parallel and whose upper band surface (11) has a wind deflection strip (42) disposed on it, which extends in the longitudinal direction of the support element (12), is provided with an attach surface (54) oriented toward the main flow of the relative wind, and is made of an elastic material, wherein the wind deflection strip (42, 142, 242) has two diverging legs (44, 46), viewed in transverse cross section, which are connected to each other at a common base (48) and whose free ends oriented toward the window (22) are supported on the wiper blade (10), and the attach surface (54) is embodied on the

outside of the one leg (44), wherein the free leg ends (50, 52) of the wind deflection strip (42, 142, or 242), at least in sections, are provided with claw-like projections (56, 58), which suitably encompass the mutually opposed outer edge strips (36) of the support element (12), and wherein the claw surfaces (60) resting against the upper band surface (11) of the support element (12) have a greater width (62) than the claw surfaces (64) engaging the lower band side (13).

45. (new) A wiper blade for cleaning windows, comprising:

a band-like, elongated, spring-elastic support element (12), whose lower band surface (13) oriented toward the window (22) has an elongated, rubber-elastic wiper strip (14), which can be placed against the window, disposed on it so that the longitudinal axes of these two parts are parallel and whose upper band surface (11) has a wind deflection strip (42) disposed on it, which extends in the longitudinal direction of the support element (12), is provided with an attach surface (54) oriented toward the main flow of the relative wind, and is made of an elastic material, wherein the wind deflection strip (42, 142, 242) has two diverging legs (44, 46), viewed in transverse cross section, which are connected to each other at a common base (48) and whose free ends oriented toward the window (22) are supported on the wiper blade (10), and the attach surface (54) is embodied on the outside of the one leg (44), wherein the upper band surface (11) of the support element (12), in its middle section, the wiper blade part (15) of a device, which is

for connecting the wiper blade (10) to a reciprocally driven wiper arm (16), is supported, wherein an end cap (38) is respectively disposed at both ends of the support element (12), wherein a section (40) of the wind deflection strip (42) is disposed between each respective end cap (38) and the device piece (15), and wherein the end caps (38) are provided with a flute (68), which extends in a projection of the flute of the attach surface (54) of the wind deflection strip.

46. (new) A wiper blade for cleaning windows, comprising:

a band-like, elongated, spring-elastic support element (12), whose lower band surface (13) oriented toward the window (22) has an elongated, rubber-elastic wiper strip (14), which can be placed against the window, disposed on it so that the longitudinal axes of these two parts are parallel and whose upper band surface (11) has a wind deflection strip (42) disposed on it, which extends in the longitudinal direction of the support element (12), is provided with an attach surface (54) oriented toward the main flow of the relative wind, and is made of an elastic material, wherein the wind deflection strip (42, 142, 242) has two diverging legs (44, 46), viewed in transverse cross section, which are connected to each other at a common base (48) and whose free ends oriented toward the window (22) are supported on the wiper blade (10), and the attach surface (54) is embodied on the outside of the one leg (44), wherein the upper band surface (11) of the support

element (12), in its middle section, the wiper blade part (15) of a device, which is for connecting the wiper blade (10) to a reciprocally driven wiper arm (16), is supported, wherein an end cap (38) is respectively disposed at both ends of the support element (12), and wherein a section (40) of the wind deflection strip (42) is disposed between each respective end cap (38) and the device piece (15), and the wiper blade part (15) of the connecting device is provided with a flute (70), which extends in a projection of the flute of the attach surface (54) of the wind deflection strip (42).

47. (new) A wiper blade for cleaning windows, comprising:

a band-like, elongated, spring-elastic support element (12), whose lower band surface (13) oriented toward the window (22) has an elongated, rubber-elastic wiper strip (14), which can be placed against the window, disposed on it so that the longitudinal axes of these two parts are parallel and whose upper band surface (11) has a wind deflection strip (42) disposed on it, which extends in the longitudinal direction of the support element (12), is provided with an attach surface (54) oriented toward the main flow of the relative wind, and is made of an elastic material, wherein the wind deflection strip (42, 142, 242) has two diverging legs (44, 46), viewed in transverse cross section, which are connected to each other at a common base (48) and whose free ends oriented toward the window (22) are supported on the wiper blade (10), and the attach surface (54) is embodied on the

outside of the one leg (44), and wherein the wiper strip (14) has a Shore hardness A of between 64 and 71, in particular 68, and the wind deflection strip (42) has a Shore hardness A of between 70 and 78, in particular 72.